


**Data Sheet** 



## **Physical Specification**

Body Quality corrosion resistant brass construction.

Lens Clear tempered glass.

Reflector High efficiency, reflective coated polycarbonate. 40ø reflector fitted

Standard. 20ø/60ø optional. Refer to Custom Configuration Matrix.

Mounting Options Ground or surface. Stake (160mm) included. Surface Mount

accessory available.

Weight (kg) 1.4

Operating Tempurature -20øC to +50øC

IP Rating IP66

## **Electrical Specification and Performance**

Input Voltage 24VDC.

Total Load 8 watts. >90 lumens per watt.

Driver Driver onboard technology.

Remote Power Supply Recommended Meanwell HLG Series 24VDC constant voltage

(sold separately). Consider adding remote control and constant

voltage.

Control Requires clean on/off signal. If switching via automation relays use

on/off. Do not use dimming relays as these may leak residual

voltage.

Dimming Triac or Dali available with approved Power Supply and compatible

dimming control

Certifications

## Finishes









■ BLK Matt Black powder coat

BZE Bronze
COP Copper
NKL Nickel

# Installation Instructions

Ground or surface. Stake (160mm) included. Surface Mount accessory available. Refer to Product Page or Technical Resources page to download Installation Sheet.




**Data Sheet** 

# **Standard or Custom Configurations**

Standard range - locally stocked item

Designed to suit a variety of residential and landscaping applications the Standard range is readily available from your local Distributor. To identify your unique ordering code simply add your chosen finish to the end of the code matrix as shown below.



Custom configuration - commercial specification

If required, we can provide a Custom solution to suit your large residential or commercial project. The following code matrix shows the options available. Production, costs and timing will vary depending on customisation. For assistance, speak to your local Commercial Distributor.

Stocked Commercial Distributor configuration shown below or Distributor customisation can be configured using this matrix. GANX 8W - cv 24VDC 2700 40 FINISH 20D GANX A8 D CV 24VDC 2700 80 BLK НХ CL 4W Х 3000 90 V 40D BZE FR **7** 60D 4000 90 COP NKL


#### **Light Performance**

Photometrics Photometrics

Diagram is based on test results as referred. Refer to Technical Resources

page to view Photometric Diagram where applicable.

IES Refer to Technical Resources page to download IES file.







**Data Sheet** 

# Warranty

5 years. Applicable on purchases from 01/01/19. Refer to Technical Resources page to download Warranty Statement.

# Wiring Guide

Refer to Technoial Resources page to download Wiring Diagram/s.




Diagram is a guide only. Wire colours and polarity may change depending on fixture and country

#### **Accessories**

Associated accessories sold separately. Refer to Accessories.



ACCENT 8 HOOD BLK



RISER 220 BLK



RISER 420 BLK



SURFACE MOUNT BLK

# **Related Items for Installation**

The following items are available to assist with installation and/or warranty compliance.



DC CABLE 2.9MM<sup>2</sup> 100M



ADHESIVE LINED END CAP 12-4MM 50 PIECES



POWER SUPPLY UNIT 60W

## Related Fittings in Range

The following fittings are also available in the Accent Lights range.



ACCENT 5 BLK