


# Accent 8 Black


Data Sheet




## Physical Specification

Body	Quality corrosion resistant brass construction.
Lens	Clear tempered glass.
Reflector	High efficiency, reflective coated polycarbonate. 40ø reflector fitted Standard. 20ø/60ø optional. Refer to Custom Configuration Matrix.
Mounting Options	Ground or surface. Stake (160mm) included. Surface Mount accessory available.
Weight (kg)	1.4
Operating Temperature	-20øC to +50øC
IP Rating	IP66

## Electrical Specification and Performance

Input Voltage	24VDC.
Total Load	8 watts. >90 lumens per watt.
Driver	Driver onboard technology.
Remote Power Supply	Recommended Meanwell HLG Series 24VDC constant voltage (sold separately). Consider adding remote control and constant voltage.
Control	Requires clean on/off signal. If switching via automation relays use on/off. Do not use dimming relays as these may leak residual voltage.
Dimming	Triac or Dali available with approved Power Supply and compatible dimming control
Certifications	

## Finishes



- BLK Matt Black powder coat
- BZE Bronze
- COP Copper
- NKL Nickel

## Installation Instructions

Ground or surface. Stake (160mm) included. Surface Mount accessory available.  
 Refer to Product Page or Technical Resources page to download Installation Sheet.

**Standard or Custom Configurations**

Standard range - locally stocked item  
 Designed to suit a variety of residential and landscaping applications the Standard range is readily available from your local Distributor. To identify your unique ordering code simply add your chosen finish to the end of the code matrix or copy the standard item code below to order:

GANL-A8-8W-2700-40D-BLK

GANL	A8	8W	2700	40D	FINISH
<b>GAN PREFIX</b>	<b>SERIES</b>	<b>TOTAL LOAD</b>	<b>LIGHT SOURCE (K)</b>	<b>REFLECTOR</b>	<b>FINISH</b>
GANL	A8	8W	2700	▼ 40D	■ BLK
					■ BZE
					■ COP
					■ NKL

Custom configuration - commercial specification  
 If required, we can provide a Custom solution to suit your large residential or commercial project. The following code matrix shows the options available for customisation. For information, speak to your local Commercial Distributor. To assist with specification, simply refer to the GANX item code below:

GANX-A8-8W-X-CV-24VDC-2700-80-40-BLK-X-CL

Stocked Commercial Distributor configuration shown below or Distributor customisation can be configured using this matrix.

GANX	A8	8W	X	CV	24VDC	2700	80	40	FINISH	X	CL
<b>GAN PREFIX</b>	<b>SERIES</b>	<b>TOTAL LOAD</b>	<b>DIMMING</b>	<b>INPUT TYPE</b>	<b>INPUT VOLTAGE</b>	<b>LIGHT SOURCE (K)</b>	<b>CRI</b>	<b>REFLECTOR</b>	<b>FINISH</b>	<b>HEX LOUVRE</b>	<b>LENS</b>
GANX	A8	8W	D	CV	24VDC	2700	80	▼ 20D	■ BLK	■ HX	○ CL
		4W	X			3000	90	▼ 40D	■ BZE	○ X	○ FR
						4000	90	▼ 60D	■ COP		
									■ NKL		

**Light Performance**


Photometrics

Photometrics

Diagram is based on test results as referred. Refer to Technical Resources page to view Photometric Diagram where applicable.

IES

IES Refer to Technical Resources page to download IES file.



**Warranty**

5 years.

Refer to Technical Resources page to download Warranty Statement.

**Wiring Guide**

Refer to Technical Resources page to download Wiring Diagram/s.




Diagram is a guide only. Wire colours and polarity may change depending on fixture and country.

**Accessories**

Associated accessories sold separately. Refer to Accessories.



ACCENT 8 HOOD BLK



RISER 220 BLK



RISER 420 BLK



SURFACE MOUNT BLK

---

**Related Items for Installation**

The following items are available to assist with installation and/or warranty compliance.



DC CABLE  
2.9MM<sup>2</sup> 100M



ADHESIVE  
LINED END  
CAP 12-4MM  
50 PIECES



POWER  
SUPPLY  
UNIT 60W

---

**Related Fittings in Range**

The following fittings are also available in the Accent Lights range.



ACCENT 5  
BLK