


Up/Down Wall Light GU10 Bronze

GANWL-MC60UD-GU10-BZE

Data Sheet




Physical Specification

| | |
|-----------------------|---|
| Body | Quality corrosion resistant brass construction. |
| Lens | Clear tempered glass. |
| Mounting Options | Surface wall mounted. |
| Weight (kg) | 1.6 |
| Operating Temperature | -20°C to +50°C |
| IP Rating | IP65 |

Electrical Specification and Performance

| | |
|---------------|--|
| Input Voltage | 240VAC to be installed by a licensed electrician only. |
| Total Load | 2 x 7 watts (maximum). Lamp not included. |
| Control | Requires clean on/off signal. If switching via automation relays use on/off. |

| | |
|----------------|---|
| Certifications |  |
|----------------|---|

Finishes



- BLK Matt Black powder coat
- BZE Bronze
- COP Copper
- NKL Nickel

Installation Instructions

Surface wall mounted.
 Refer to Product Page or Technical Resources page to download Installation Sheet.

Standard or Custom Configurations

Standard range
 Designed to suit a variety of residential and landscaping applications the Standard range is readily available from your local Distributor. To identify your unique ordering code simply add your chosen finish to the end of the code matrix as shown below.

| | | | | |
|---------------|---------|-------|--------|--|
| GANWL | -MC60UD | -GU10 | - | |
| GAN PREFIX | SERIES | LAMP | FINISH | |
| GANWL | MC60UD | GU10 | BLK | |
| | | | BZE | |
| | | | COP | |
| | | | NKL | |

x2 LED 7W
 GU10 (Max) lamps
 not included.
 Refer to installation
 instructions.

Up/Down Wall Light GU10 Bronze

GANWL-MC60UD-GU10-BZE

Data Sheet

Warranty

5 years (fitting only).
 Refer to Technical Resources page to download Warranty Statement.

Wiring Guide

Refer to Technical Resources page to download Wiring Diagram/s.

Accessories

Associated accessories sold separately. Refer to Accessories.



LED GU10
 6.5W WARM
 WHITE

Related Items for Installation

The following items are available to assist with installation and/or warranty compliance.



DC CABLE
 2.9MM² 100M



ADHESIVE
 LINED END
 CAP 6-2MM
 50 PIECES



LED GU10
 6.5W WARM
 WHITE



POWER
 SUPPLY
 UNIT 60W

Related Fittings in Range

The following fittings are also available in the Wall Lights GU10 range.



WALL DOWN
 LIGHT GU10
 FB