


Data Sheet



Physical Specification

Body Quality corrosion resistant brass construction.

Lens Clear tempered glass.

Mounting Options Surface wall mounted.

Weight (kg) 1.6

Operating Tempurature -20øC to +50øC

IP Rating IP65

Electrical Specification and Performance

Input Voltage 240VAC to be installed by a licensed electrician only.

Total Load 2 x 7 watts (maximum). Lamp not included.

Control Requires clean on/off signal. If switching via automation relays use

on/off.

Certifications

Finishes









BLK Matt Black powder coat

BZE Bronze
COP Copper
NKL Nickel

Installation Instructions


Surface wall mounted.

Refer to Product Page or Technical Resources page to download Installation Sheet.

Standard or Custom Configurations

Standard range - locally stocked item

Designed to suit a variety of residential and landscaping applications the Standard range is readily available from your local Distributor. To identify your unique ordering code simply add your chosen finish to the end of the code matrix as shown below.





Data Sheet

Warranty

5 years (fitting only).

Refer to Technical Resources page to download Warranty Statement.

Wiring Guide

Refer to Technoial Resources page to download Wiring Diagram/s.

Accessories

Associated accessories sold separately. Refer to Accessories.



LED GU10 6.5W WARM WHITE

Related Items for Installation

The following items are available to assist with installation and/or warranty compliance.



DC CABLE 2.9MM² 100M



ADHESIVE LINED END CAP 6-2MM 50 PIECES



LED GU10 6.5W WARM WHITE

Related Fittings in Range

The following fittings are also available in the Wall Lights GU10 range.



WALL DOWN LIGHT GU10 BLK