


Up/Down Wall Light MR16 Bronze


Data Sheet



Physical Specification

| | |
|-----------------------|---|
| Body | Quality corrosion resistant brass construction. |
| Lens | Clear tempered glass. |
| Mounting Options | Surface wall mounted. |
| Weight (kg) | 1.6 |
| Operating Temperature | -20°C to +50°C |
| IP Rating | IP65 |

Electrical Specification and Performance

| | |
|---------------------|---|
| Input Voltage | 12-24V AC/DC |
| Total Load | 2 x 7 watts (maximum). Lamp not included. |
| Remote Power Supply | Ensure remote ELV power supply and lamp match before use (sold separately). |
| Control | Requires clean on/off signal. If switching via automation relays use on/off. |
| Certifications |  |

Finishes



- BLK Matt Black powder coat
- BZE Bronze
- COP Copper
- NKL Nickel

Installation Instructions

Surface wall mounted.
 Refer to Product Page or Technical Resources page to download Installation Sheet.

Standard or Custom Configurations

Standard range - locally stocked item
 Designed to suit a variety of residential and landscaping applications the Standard range is readily available from your local Distributor. To identify your unique ordering code simply add your chosen finish to the end of the code matrix as shown below.

| | | | |
|-------------------|---------------|--|---------------|
| GANWL | MC60UD | MR16 | |
| GAN PREFIX | SERIES | LAMP | FINISH |
| GANWL | MC60UD | MR16 | BLK |
| | | x2 LED 7W MR16 (Max) lamps not included. Refer to installation instructions. | BZE |
| | | | COP |
| | | | NKL |

Up/Down Wall Light MR16 Bronze

Data Sheet

Light Performance


Photometrics

Photometrics

Diagram is based on test results as referred. Refer to Technical Resources page to view Photometric Diagram where applicable.

IES

IES Refer to Technical Resources page to download IES file.



Warranty

5 years (fitting only).

Refer to Technical Resources page to download Warranty Statement.

Wiring Guide

Refer to Technical Resources page to download Wiring Diagram/s.

Accessories

Associated accessories sold separately. Refer to Accessories.



LED MR16
6W WARM
WHITE



POWER
SUPPLY
UNIT 60W

Up/Down Wall Light MR16 Bronze

Data Sheet

Related Items for Installation

The following items are available to assist with installation and/or warranty compliance.



DC CABLE
2.9MM² 100M



ADHESIVE
LINED END
CAP 6-2MM
50 PIECES



LED MR16
6W WARM
WHITE



POWER
SUPPLY
UNIT 60W

Related Fittings in Range

The following fittings are also available in the Wall Lights MR16 range.



WALL DOWN
LIGHT MR16
BZE